The PROVEN Way to Reduce **Catheter Related Blood Stream Infections**

How to Place **BIOPATCH[®]** Protective Disk with CHG



LINE INSERTION: Leave a minimum of 1.25cm of catheter to allow for proper cleaning and to apply BIOPATCH®.



CLEANING: Prepare site with antiseptic and wait until the skin is completely dry.



APPLICATION of BioPatch®: Apply BIOPATCH® printed side up with radial slit approximated and aligned no more than 5° from catheter tubing exiting the body (for ease of removal). Do not peel printed side from BioPatch?



DRESSING: Ensure BIOPATCH® has 360° contact with skin around catheter. Cover with transparent film dressing.



REMOVAL: When slit is aligned correctly, BIOPATCH® will remain attached to the transparent film dressing and removal will be simultaneous.

BioPatch® Applications



Central Venous Catheters



Peripheral IVs



Dialysis Catheters



Epidural Catheters

BIOPATCH® Size Selections


	BIOPATCH P BIOPATCH P BIOPATCH CHITUP BIOPATCH BIOPATCH DUP BIOPATCH DUP BIOPATCH TUP BIOPATCH TUP BIOPATCH	UE Brone	ATCH <u>11</u> P BIOP ATCH <u>11</u> P BIOP CH <u>11</u> P BIOPATCH DEPATCH D
ORDER CODE	4150	4151	4152
SIZE	1" disk (2.5 cm) w/4.0 mm center hole	3/4" disk (1.9 cm) w/1.5 mm center hole	1" disk (2.5 cm) w/7.0 mm center hole
FRENCH SIZE RANGE	6-12 Fr	<6 Fr	13-20 Fr
AVERAGE AMOUNT OF CHG PER DRESSING	92 mg	52.5 mg	86.8 mg
QUANTITY PER CASE	10/box 4 boxes/case; 40	10/box 4 boxes/case; 40	10/box 4 boxes/case; 40



For Full Prescribing Information or technical support, call 1-877-ETHICON (1-877-384-4266) or visit www.BIOPATCH.com

To place an order, call 1-800-255-2500

References 1. Maki DG, Mermel L, Genthner D, Hua S. Chiacchierini RP. An evaluation of BioPATCH® Antimicrobial Dressing compared to routine standard care in the prevention of catheter-related bloodstream infection. Johnson & Johnson Wound Management, a division of Ethicon, Inc. 2000. Data on file.



© Ethicon, Inc. 2012 BP-126-12

ETHICON Biopatch[®] Products



Arterial Catheters



Implanted Venous Ports



PICC Lines



Drains

Tips & Troubleshooting



UPSIDE DOWN: The white side of BIOPATCH® must face down. **ВюРатсн**[®] should be changed.



ON TOP OF LINE: Ensure 360° contact with skin around catheter. **ВюРатсн® should be changed.**





SLIT NOT APPROXIMATED:

SATURATED: BIOPATCH® can absorb 8 times its weight in fluid. In this case, foam has become saturated. **ВюРатсн® should be changed.**

